BPA Change Sheet Calleguas Creek Nitrogen TMDL October 24, 2002

Document	Page No.	Descri	ption of Ch	nange and	l Justifica	ntion
Numeric Target	10-105	This section was revised to clarify that the numeric targets are expressed as concentrations that are based on the water quality objectives and the margin of safety: "The numeric targets for ammonia (chronic) range from 1.7 mg/L to 3.5 mg/L and from 3.2 mg/L and 9.5 mg/L (acute) depending on location. Numeric targets to address narrative objectives required to protect warm freshwater and wildlife habitat are believed to be sufficient to implement the narrative objectives and may be revised based on the results of monitoring and studies conducted pursuant to the implementation plan."				
Waste Load Allocations (for point sources)	10-106	Revised waste load all concentrations and ref with Regional Board F. The Basin Plan Ameriand wasteload allocation record, proposed waster POTWs Hill Canyon WWTP Simi Valley WQCP Moorpark WWTP Camarillo WRP Camrosa WWTP Olsen Rd. WRP The ammonia objective as calculated in according for compliance purposed daily effluent limits. Oprovided in the Staff F.	Resolution (adment clear ons. The median local allocal Ammonia AMEL (mg/L) 3.14 2.35 2.63 3.50 2.98 N/A re is based clance with the ses, Resolut Calculation	tion of an 12-011:. rly identifumeric tarations (W NO ₃ -N (mg/L) 9.0 9.0 9.0 9.0 9.0 N/A on the average the Resolution 02-01	fies the TM rget using (LAs) are 1 NO ₂ -N (mg/L) 0.9 0.9 0.9 0.9 N/A rage montation 02-0 1 also pro	LA in conformance MDLs and all load the entire historical listed as follows: NO ₃ -N+NO ₂ -N (mg/L) 9.0 9.0 9.0 9.0 9.0 9.0 N/A Chly effluent limit 11. It is noted that vides maximum
Load Allocation (for non point sources)	10-106	Incorporation of non point source load allocations expressed by concentrations. The source anlaysis indicates that an agricultural discharge is the major non-point source of oxidized nitrogen to Calleguas Creek and its				

¹ AMEL: Average monthly effluent limitation

Document	Page No.	Description of Change and Justification			
		tributaries. This source is particularly significant in Revolon Slough and other agricultural drains in the lower Calleguas watershed where there are no point sources of ammonia and oxidized nitrogen. Load allocations for other non-point sources are: Nonpoint Source Nitrate-N + Nitrite-N			
		Agriculture 9.0 Other Nonpoint Source 9.0			
Implementation	10-107	Revised the implementation plan to allow additional time for POTW comply with the TMDL waste load allocations. Several of the POTWs in the Calleguas Creek watershed will require additional time to meet the oxidized nitrogen (nitrate, nitrite, and nitr + nitrite) waste load allocations. To allow time for completion of denitrification facilities which are integral to this TMDL, the amendment to the Basin Plan made by this TMDL allows for higher interim loads that translate as the interim effluent limits as follows for period of four years from the effective date of the TMDL: POTWs Interim Limits* for Nitrate-N + Nitrite-N Monthly Average Daily Maximum (mg/L) (mg/L) Hill Canyon WWTP 36.03 38.32 Simi Valley WQCP 31.60 32.17 Moorpark WWTP 31.5 32.01 Camarillo WRP 36.23 37.75 Olsen Rd. WRP N/A N/A * The monthly average and daily maximum interim limits are based the 95th and 99th percentiles of effluent performance data reported in Calleguas Creek Characterization Study			